

487 Onward

S P E C I F I C A T I O N S

For

Fast Cruising Yacht for thirty foot class.

-----oOo-----

Length on deck, - - - - - about 44 feet.

Length on water line, - - - - - 29 ft. 9 inches.

Extreme beam, - - - - - 10 ft.

Depth of hull, - - - - - about 5 ft. 9 inches.

Keel, timbers, deck-beams and carlins to be white oak.

Planking to be double to below the turn of bilge, the outer thickness to be of mahogany and the inner thickness to be white pine or cypress.

Planking on bottom, below the turn of bilge, to be yellow pine single thickness and caulked.

Deck to be of white pine, covered with canvas and painted.

Hull to be strapped with Tobin bronze.

All fastening to be of copper and bronze.

Rudder stock, and hangings, to be Tobin bronze.

Nearly all of the ballast, which is to be Lead, will be moulded to form and will be secured to the bottom of keel.

Yacht to be rigged complete with all necessary spars, standing and running rigging, and blocks.

Sails to consist of mainsail, forestaysail, jib No.1, jib No.2, spinnaker, baloon jib and trysail.

(2)

Jib to be set flying so that it can be easily taken off.

Forestaysail to be fitted with a boom.

Mainsail to have double ended sheets same as "ANGATOK".

Main boom, and staysail boom, to be fitted with a sail slide.

Blocks and cleats to be of bronze.

Rudder to have a hinged tiller.

Equipment to consist of one steel anchor and manilla cable, two mooring lines, pump, bucket, sponge, bailer, boat hook, lead and line, side lights and lanterns.

Cabin and cock-pit to be furnished with cushions.

A water closet will be placed in the forward part of the cabin and properly partitioned off.

X Water Tanks

An ice chest to be placed under the cock-pit. *Water Tanks Joints to be made to unscrew from pipe, and all arranged so as easily cleaned. A small cold cupboard in front of ice chest.*

Stern sheets to be partitioned off, door on one side to bolt on the inside, the other door to lock from the outside.

A stand will be fitted in the cabin, to hold an oil stove, and covered with zinc where needed.

Mainsail, and forestaysail, will be furnished with covers, ^{*If water proofed done*} and [^] the ^{# 2 jib} balloon jib and spinnaker, also trysail, with bags.

Yacht to be painted white with name, in gilt letters, on stern.

*Awning A cover cock pit
Portable table in cabin.*